

# CITIZEN

**Designed and built for performance**  
Unique design in white or black, with outstanding features and reliability



### **Stylish, fast and compact**

The CL-E321's compact, modern, functional design takes up very little desk space, is easy to use and is also perfectly at home in any location, from warehouses to hospitals. It also has a fast print speed of 8 inches-per-second, is quick to setup and to load with media.

### **Well connected**

The CL-E321 features on-board LAN, USB and Serial interfaces. All industry-standard emulations are fully supported, with the option of remote operation via a web browser, using the Citizen LinkServer™ management tool.

### **Easy operation**

The CL-E321 is simple to use and intuitive, ensuring users waste no time when changing labels or adjusting settings.

## CL-E321

**Label, Desktop**

### **Applications**

- Courier
- Logistic / Transport
- Manufacturing
- Healthcare



The CL-E321 has a wide opening (180°) Hi-Lift™ case, and uses full size, 300m ribbons with standard 1 inch cores.

TOMORROW'S PRINTING TODAY

# CITIZEN



Ethernet LAN, USB and Serial interfaces as standard

## Specifications

Model	CL-E321
Printing Technology	Thermal Transfer + Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	8 inches per second (200 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	1 - 4.6 inches (25 - 118 mm)
Roll Size (max), Core Size	Inside diameter 5 inches (125 mm) Core size 1 inch (25mm)
Media Thickness (min to max)	63.5 to 190 µm
Media Length (min to max)	0.25 to 100 inches (6.35 to 2540 mm)
Media Sensor	Fully adjustable gap and reflective black mark
Main Interface	Triple interface USB 2.0, RS-232 and 10/100 Ethernet
Ribbon size	2.6 inches (60 mm) maximum outside diameter. 300 metres length. 1 inch (25 mm core)
Ribbon winding & type	Ink side out. Wax, Wax/Resin or Resin Type
Mechanism	Clamshell, easy-to-load, wide opening design
Control panel	One LED, Control key: FEED
Emulations (Languages)	Datamax® DMX, Cross-Emulation™ - autoswitch between Zebra® and Datamax® emulations, Zebra® ZPL2®, CBI™ BASIC Interpreter, Eltron® EPL2®
Drivers and software	Free-of-charge on CD with printer, including support for various platforms
Flash (Non-Volatile Memory)	16 MB total, 4MB available for user

Citizen Systems Europe GmbH, Elizabeth House, 56-60 London Road, Staines-Upon-Thames, TW18 4HF, United Kingdom

Size (W x D x H) and

170 x 200 x 170 mm (6.7 x 7.9 x 6.7 inches)

## CL-E321

Label, Desktop

### Features & Benefits

- Paper load: Hi-Lift™ mechanism and ClickClose™ closure
- Printing Speed: Ultra fast print out - up to 200mm per second (8 inches per second)
- Media support: Large media capacity - holds rolls up to 5 inches (127 mm)
- ENERGY STAR® compliant
- Small footprint



Media loading is simplified still further through the use of innovative ribbon holders, with a ClickClose™ closure mechanism ensuring complete reliability.

CITIZEN SYSTEMS EUROPE GMBH

# CITIZEN

CL-E321

Label, Desktop

<b>Model</b>	CL-E321
<b>EMC and safety standards</b>	CE, TUV, UL, FCC, VCCI

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0